



### English Translation

This translation was presented to the VdTÜV. VdTÜV takes no responsibility for the correctness of the translation. Hints (information) for improvement should be addressed to the VdTÜV. In case of doubt or dispute, the latest edition of the German text only is valid.

### Preamble

This Merkblatt was prepared by the Verband der TÜV e. V. (VdTÜV) in cooperation with

- the Deutscher Wasserstoffverband e. V. (DWV)
- the Mineralölwirtschaftsverband e. V. (MWV)
- the specialists for technical occupational safety and health and plant safety from the Länderausschuss für Arbeitsschutz und Sicherheitstechnik – LASI
- the manufacturers of hydrogen fueling stations and hydrogen-powered vehicles

on the basis of *BetrSichV*, *TRG 404*, the unpublished *TRG 406* draft and the current state of the art.

This Merkblatt was prepared based to the best of the authors' knowledge and belief and represents, in their view, good engineering practices.

The requirements contained in this Merkblatt represent adequate safety solutions for customary situations. All liability is disclaimed, even with respect to the technical or factual accuracy of the information contained in this agreement. Users are also responsible for clarifying all patent and other property rights on their own.

This Merkblatt is updated regularly to reflect changes in good practices. Suggested modifications to the document can be sent to the publisher:

**Verband der TÜV e. V.  
Friedrichstrasse 136  
10117 Berlin, Germany**

### Table of contents

1	Scope
2	Definitions
2.1	Hydrogen fueling stations
2.2	Dispensing devices
2.3	Instrumentation and control
2.4	Explosive atmosphere
2.5	Hazardous places
2.6	Control area
2.7	Protective measures
2.8	Unsupervised operation (when dispensing to third parties)
2.9	Safety measures
2.10	Precooling system